

TD Dryers – Stack & Single Pocket

Wascomat commercial TD dryer models are precision-engineered for efficiency, ease of use, & superior drying results. Our single pocket dryers now have easy to use Compass Pro control. Wascomat dryers are your best choice for reliability, durability, & customer satisfaction. Perfect for coin/card laundries, customers love the fast drying & user-friendly controls.



Features and benefits:

- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the fastest drying with lowest energy consumption
- Extra large doors make loading and unloading easy
- Convenient access to parts
- Easy to clean lint screen – best in the industry
- Quiet operation. Our dryers are designed to keep noise level below 70 dB (A)
- Reverse drum operation (option) minimizes tangling and wrinkling, and improves dryer efficiency
- Sturdy drum suspension with double-sealed bearings and belt drive

Single Pocket Dryer features:

- **Axial airflow** and tight construction for extremely low energy consumption
 - Dries 12% faster, saving 25% in gas
- **Compass Pro** program control
 - Large and clear display with control knob for easy program selection
 - Easy to program, easy access to USB
 - Language selection
 - Service program for adjustment of parameters
- **Selecta II**
 - 4 temperature settings
 - Displays remaining drying time.
 - Coin, token, debit card compatible
 - Complete diagnostics & service model
- Top Exhaust Kit (optional)

Wascomat dryers offer reliability, durability and significant energy savings for self-service laundries.

TD DRYER CONTROLS

Compass Pro

- Compass Pro available on single pocket Wascomat dryers.

Selecta II Coin/Card

- Selecta II on 30x30 Stack and 45x45 Stack dryers.

30x30, 45x45, 35, 67 and 83 lb. capacities. Available in stainless or white front panel. Coin and card-ready.

| Wascomat Dryer Models | TD30x30 | | TD45x45 | | TD35 | | TD67 | | TD83 | |
|--|----------------|-------|------------------------|---------|-----------------|------|------------------|------|------------------|------|
| Capacity (lb/kg) | 2x30 | 2x30 | 2x45 | 2x20.41 | 35 | 16.1 | 67 | 30.5 | 83 | 37.5 |
| Width (in/mm) | 31 1/8 | 790 | 34 1/4 | 870 | 27 15/16 | 710 | 37 13/16 | 960 | 37 13/16 | 960 |
| Depth (in/mm) | 43 11/16 | 1110 | 52 5/8 | 1336 | 45 1/2 | 1155 | 51 3/4 | 1315 | 59 7/16 | 1510 |
| Depth with door open (in/mm) | 72 7/16 | 1840 | 85 5/8 | 2175 | 68 5/16 | 1735 | 83 11/16 | 2125 | 91 5/16 | 2320 |
| Height Overall (in/mm) | 76 3/8 | 1940 | 81 7/8 | 2078 | 65 15/16 | 1675 | 73 7/16 | 1855 | 73 7/16 | 1855 |
| Height without heating unit (in/mm) | n/a | | n/a | | n/a | | n/a | | n/a | |
| Door opening diameter (in/mm) | 22 7/8 | 580 | 27 | 686 | 22 13/16 | 580 | 31 7/8 | 810 | 31 7/8 | 810 |
| Cylinder volume (ft ³ /l) | 10.6 | 300 | 14.6 | 414 | 10.2 | 290 | 19.4 | 550 | 23.8 | 675 |
| Grated Weight (lb/kg) | 693 | 315 | 865 | 392 | 518 | 235 | 717 | 325 | 827 | 375 |
| Utility Connections | | | (2) 8" or (1) 10" | | | | | | | |
| Exhaust duct diameter (in/mm) | 8 | 200 | (2) 203mm or (1) 254mm | | 8 | 200 | 10 | 250 | 10 | 250 |
| Gas connection | 1/2 NPT | | 3/4 MNPT | | 1/2 NPT | | 1/2 NPT | | 1/2 NPT | |
| Energy Data | | | | | | | | | | |
| Gas (Btu/hr) | 2x71,700 | | 2x94,000 | | 71,700 | | 112,700 | | 143,400 | |
| Airflow (ft ³ /min / m ³ /hr) (gas heat) | 2x354 | 2x600 | 2x600 | 2x1020 | 360 / 610 | | 550 / 940 | | 670 / 1140 | |
| 3000Electric (kW) @ 208-240V/3Ø | 2x18 | n/a | 18 | 30 | 13.5 or 18 | | 24 or 32 | | 24 or 32 | |
| Airflow (ft ³ /min / m ³ /hr) (elec. heat) | 2x354 | 2x600 | n/a | | 325 / 550 | | 550 / 940 | | 670 / 1140 | |
| Steam (lb/hr /kg/hr) (approximate) | n/a | | n/a | | 80 / 36 | | 118 / 54 | | 150 / 68 | |
| Airflow (ft ³ /min / m ³ /hr) (steam heat) | n/a | | n/a | | 405 / 690 | | 635 / 1080 | | 810 / 1380 | |
| Electrical Requirements | | | | | | | | | | |
| Current, gas or steam, 120 V/60Hz(full load/circuit breaker) | 2x9A / 2x15A | | 2x12A / 2x15A | | 7.5A (15A) | | 12A (20A) | | 12A (20A) | |
| Current, gas or steam, 208-240 V/60Hz/1Ø(full load/circuit breaker) | 2x4.5A / 2x15A | | 5.50A / 15A | | 3.5A (15A) | | 8.5A (15A) | | 8.5A (15A) | |
| Current, gas or steam, 208-240 V/60Hz/3Ø(full load/circuit breaker) | n/a | | n/a | | 3.75A (15A) | | 10A (15A) | | 10A (15A) | |
| Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker) | 2x50 / 2x65 | | n/a | | 14.4-18.9 (60A) | | 26.1-34.4 (110A) | | 26.1-34.4 (110A) | |
| Alternate Voltages | | | | | | | | | | |
| Alternate voltages available. Contact Laundrylux Sales Department for information. | | | | | | | | | | |
| Supply Pressures | | | | | | | | | | |
| Natural Gas (inches H2O/mbar) | 6-10/ 15-25 | | 6-12/ 15-30 | | 3.5-10.5 / 9-26 | | 3.5-10.5 / 9-26 | | 3.5-10.5 / 9-26 | |
| Propane (inches H2O/mbar) | 10-13 / 25-30 | | 11-13 / 28-33 | | 8-13 / 20-32 | | 8-13 / 20-32 | | 8-13 / 20-32 | |
| Exhaust back pressure (inches H2O/mbar) (max) | 1.57 | 3.9 | 0.6 | 1.5 | 2.2 | 5.5 | 2.6 | 6.48 | 3 | 7.5 |

Note: TD45x45 45 lb. stack dryer - 208 volt, 1-phase not available. Use 120 volt model for 208 volt applications.

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

**Call today for information on the full line of
Wascomat Commercial Laundry Equipment and low-cost financing and leasing.**



Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
Sales & Administration: Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com
Parts: Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com
Technical Support: Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com
En Mexico: Llame gratis a este numero 001-800-010-1010



TD45x45 is CSA certified. Other TD dryers are ETL certified.